

to be CORK

CORK STOPPERS

MICRO-AGGLOMERATED, FINISHED



Agglomerated cork cylinder with 90% of its granules between 0.25mm and 2.5mm

Manufactured according to UNE standards.

Recommended use: *tables wines, fast-rotation wines and young wines.*

CHARACTERISTICS

PARAMETERS

SPECIFICATIONS



DIMENSIONS

Length
Diameter

38 to 49 mm \pm 0,5 mm
23,5 to 24 mm \pm 0,3 mm



PHYSICAL

Density
Humidity
Capillarity
Extraction force
Immediate diametral recovery
5 minute diametral recovery
1 hour diametral recovery
Deagglomeration

240 – 350 Kg/m³
3 – 8%
 \leq 2,5 mm
15 – 40 daN
 \geq 86%
 \geq 90%
 \geq 95%
Non-existent



SENSORIAL

Smell

Neutral



CROMATOGRAPHIC

TCA

According to client's protocol



CHEMICAL

Residual oxidants

Negative

QUALITIES

We have all the standard qualities available. We can also customise the corks according to the specific quality of each client.

ANALYSIS METHOD

All analyses are carried out according to standards UNE 56921, UNE 56927, UNE 56928 and UNE 56929.

Other parameters or analyses according to the specifications of each client.

CORK

For more information:

info@tobecork.com
www.tobecork.com