

to be CORK

CORK STOPPERS

3-PIECE (1+1), FINISHED



Agglomerated cylinder comprising natural cork with a disc of natural cork at each end.
Manufactured according to UNE standards.
Recommended use: *tables wines, fast-rotation wines and young wines.*

CHARACTERISTICS

PARAMETERS

SPECIFICATIONS



DIMENSIONS

Length
Diameter
Thickness of discs

44 mm o 45 mm ± 0,5 mm
23,5 mm ± 0,4 mm
≥ 4,0 mm



PHYSICAL

Density
Humidity
Capillarity
Extraction force
Immediate diametral recovery
5 minute diametral recovery
1 hour diametral recovery
Deagglomeration

235 – 315 Kg/m³
4 – 8%
≤ 2,5 mm
20 – 40 daN
≥ 87%
≥ 91%
≥ 93%
Non-existent



SENSORIAL

Smell

Neutral



CROMATOGRAPHIC

TCA

According to client's protocol



CHEMICAL

Residual oxidants

Negative

QUALITIES

We have all the standard qualities available. We can also customise the corks according to the specific quality of each client.

ANALYSIS METHOD

All analyses are carried out according to standards UNE 56921, UNE 56927, UNE 56928 and UNE 56929.

Other parameters or analyses according to the specifications of each client.

CORK

For more information:

info@tobecork.com
www.tobecork.com